



超小型电感式接近传感器

DC三线

Φ3*25(齐平) Φ4*25(齐平)

CE
RoHS



产品尺寸 安装方式 感应距离 可靠感应距离 标准检测物 外壳材质 是否带LED灯 工作电压 连波 无负载电流 最大负载电流 漏电流 电压降 开关频率 响应时间 开关迟滞 重复精度 防护等级 工作环境温度 温度漂移 短路保护 过载电流保护点 感应面材质 连接方式 重量 认证	Φ3*25			Φ4*25			
	齐平			齐平			
	0.6mm±10%	0.8mm±10%	1.0mm±10%	0.8mm±10%	1.0mm±10%	1.2mm±10%	1.5mm±10%
	0-0.48mm	0-0.64mm	0-0.8mm	0-0.64mm	0-0.8mm	0-0.96mm	0-1.2mm
	3*3*1mm(Fe37)			4*4*1mm(Fe37)			4.5*4.5*1mm(Fe37)
	不锈钢			不锈钢			
	黄色LED			黄色LED			
	10-30V DC			10-30V DC			
	<10%			<10%			
	<10mA			<10mA			
	100mA			150mA			
	<0.01mA			<0.01mA			
	<1.5V			<1.5V			
	2KHz	1.5KHz	1KHz	2KHz	2KHz	1.5KHz	1KHz
	0.1ms	0.1ms	0.2ms	0.1ms	0.1ms	0.2ms	0.2ms
	<15%(Sr)			<15%(Sr)			
	<5.0%(Sr)			<5.0%(Sr)			
	IP67			IP67			
	-25℃...+70℃			-25℃...+70℃			
	<10%(Sr)			<10%(Sr)			
	—			Yes			
	—			260mA			
	Epoxy			PA66			
	Φ2.5mm 2M PVC电缆线, 3*0.15mm ²			Φ2.5mm 2M PVC电缆线, 3*0.15mm ²			
	约19.2g			约21.5g			
	CE RoHS			CE RoHS			

产品尺寸仅供参考
以实际测量为准。

单位:mm

